

DNA 1000.2 HE

The world's most advanced high-end amplifier

Your system is perfectly adjusted to:

- individual sound preferences
- listening levels
- musical styles
- loudspeaker characteristics
- room acoustics on site

Three modes of operation are possible with the DNA1000.2 HE:

- Stereo: 2 x 500 Watts sinus
- Double mono: 500 W + 500 W sinus
- Mono: 1000W sinus



Total system power
230 V

2 x 500 W @4 Ohms
2 x 250 W @ 8 Ohms
1 x 1050 W @ 4 Ohms
1 x 900 W @ 8 Ohms
Standby Power 0,33 W
Mute Power 6,8 W
Idle Power 9,2 W
Power Factor 0,97
Power dissipation max 42 W



Total system power
110 V

2 x 500 W @4 Ohms
2 x 250 W @ 8 Ohms
1 x 700 W @ 4 Ohms
1 x 700 W @ 8 Ohms
Standby Power 0,23 W
Mute Power 6,8 W
Idle Power 9,2 W
Power Factor 0,98
Power Dissipation max 42 W

Dimensions (W/H/D)

360 / 155* / 255* mm
*plus 15 mm for the stands

Weight

16,3 kg

Finish

Cabinet:

black

Analog Input

2 x XLR female

Ethernet AVB

Connectivity Network

100 MBit / s Fast Ethernet

Switch

RJ45/ Cat 5

Streaming Technology

3 port Fast Ethernet Switch, AVB compliant
Ethernet AVB compliant
500 ns synchronicity
2 ms latency
2 streams/8 ch per stream

Comand & Control

UNOS

DSP channels

1 x Input, 2 x Output