

CCMI6-P

PASSIVE
IN CEILING MONITOR



Speaker type Loudspeaker	Time coherent 6.5" coax point-source Zeit-richtige 16,5 cm Coax- Einpunktschallquelle
Use Case Verwendung	In Ceiling Decken Einbau
Passive Active	Passive Passiv
Frequency Range Frequenzbereich	60 Hz - 20 kHz / -3 dB
Sensitivity Wirkungsgrad	87dB / 1W/m
Power handling Belastbarkeit	80 W RMS - 160 W Peak
Impedance Impedanz	4 Ω
Motor Antrieb	Woofer and Tweeter: Neodymium
Woofer Tieftöner	6,5" carbon
Tweeter Hochtöner	1,1" soft dome
Dispersion pattern Abstrahlwinkel	120°
Speaker In Lautsprecher Eingang	Push on terminals up to AWG14 Klemme bis 2,5 mm ²

Mounting Montage	Dogfeet clamps Klemmvorrichtung
Cut out diameter Ausschnitt Durchmesser	8,1 " 206 mm
Mounting depth Einbautiefe	1,6 " 40 mm
Grille Dimensions Ab- deckung Abmessungen	9,0 " 228 mm
Grille mounting Ab- deckgitter Befestigung	Magnetic Magnetisch
Grille finish Ab- Abdeckgitter Farbe	White, can be overpainted Weiß, überlackierbar
Weight Gewicht	1,98 lbs 0,9 kg