



Speaker type	Time coherent 10" coax point-source
Principle	Vented
Passive Active	Passive
SPL	Calculated data 120 dB cont. / 123 dB peak
Frequency range	Calculated data 75 Hz - 20 kHz / -3 dB
Efficiency	98 dB / 1W/m
Power handling	500W
Impedance	8 Ω
Woofer	10"
Tweeter	1" Compression driver
Directivity horizontal x vertical in Deg°	85° x 85°
Input terminal	One 4-conductor Phoenix 12 AWG (3,3 mm²) push on binding post
Enclosure	MDF
Width	14,70" 360 mm vertical 14,7 0" 360 mm horizontal
Hight	15,04" 382 mm vertical 8,62" 219 mm horizontal
Depth (without grille)	8,62" 219 mm vertical 15,04" 382 mm horizontal
Weight	28,66 lbs 13 kg
Finish	Matte black

Custom colour options	Piano lacquer: colour of choice, matt or other finishes upon request
Shape customization	Upon request
Mounting	Metal wall or ceiling mounting brackets that allows to angle the speaker further in two axes + 8 wall mount brackets, which allow to hang the speaker in multiple ways on the wall + VESA 200 x 100 mounting points

The THE10 PASSIVE WEDGE 30 is supplied with a front cover as standard

