

ascendo

ELEVATE YOUR SOUND

AIA4-6004



DATA SHEET

AUDIO

Table 1. *Inputs*

Channels	4
Signal-to-Noise Ratio	101 dB
Sensitivity	2 V

Table 1. *Outputs*

Output Power	230 V @ 4 Ω	230 V @ 8 Ω
	4 x 1500 W	4 x 800 W
Frequency response	20 Hz – 20 kHz	
Protection	Soft-start, Turn-on Turn-off transients, Over-heating, DC, RF, Short-circuit, Open or mismatched loads, ICL™, PMS™	
Damping factor	>400	
Total Harmonic Distortion	<0.05 %	
Intermodulation Distortion	<0.05 %	
Crosstalk 20Hz – 1kHz	>75 dB	
Voltage Gain	32 dB	

AC MAINS POWER

Operating Voltage	90 - 265 VAC
Power On Idling (@230V)	0.5 A
1/8 Rated Power (230V @ 4Ω)	4.5 A

CONNECTORS



Figure 1. AIA4-6004 connectors

Audio signal input connectors	Neutrik XLR
Audio signal output connectors	Neutrik XLR
Speaker connector	Neutrik speakON®

THERMAL

Thermal dissipation	Fan, variable speed, temperature controlled front to rear airflow			
	230 VAC		120 VAC	
idle	216 BTU/h	54 kcal/h	216 BTU/h	54 kcal/h
1/8 power @ 8Ω	419 BTU/h	106 kcal/h	419 BTU/h	106 kcal/h
1/8 power @ 4Ω	786 BTU/h	198 kcal/h	786 BTU/h	198 kcal/h

USER INTERFACES

Hardware	Status LEDs, Potentiometers, Power button
----------	---

DIMENSIONS / WEIGHT





Figure 2. AIA4-6004 dimensions

Dimensions (W/H/D) mm	483 89 416 (2RU)
Dimensions (W/H/D) Inch	19 3 1/2 16 3/8 (2RU)
Packing Dimensions W/H/D) mm	650 270 600
Packing Dimensions (W/H/D) inch	25 9/16 10 5/8 23 5/8
Weight	18.74 lbs 8.5 kg
Gross Weight	27.56 lbs 12.5 kg



CE



ASCENDO Immersive Audio GmbH
Adlerstrasse 2, Gebäude C, EG
D-91560 Heilsbronn · Germany
Tel.: +49 9872-9 537 157 · www.aia-cinema.com

