



Stealth PA1 Class-D monoblock power amplifier

Combines compact size, high efficiency, and excellent sound quality in a single convenient package.

Features:

- Compact 1U class-D monoblock
- 140W RMS into 8 Ω or 300W RMS into 4 Ω
- ICEpower 300ASC amplifier module
- Single XLR input

Specifications:

- Channels: 1
- Output power:
 - 140W RMS into 8 Ω @ 1 kHz at 1% THD
 - 135W RMS into 8 Ω @ 0.1% THD
 - 300W RMS into 4 Ω @ 1 kHz at 1% THD
 - 270W RMS into 4 Ω @ 0.1% THD
 - 450W RMS into 2.7 Ω @ 1 kHz at 1% THD
- Full power bandwidth: 20 Hz - 20 kHz
- THD+N: 0.005% at 1 kHz at 1 watt into 4 Ω
- S/N ratio:
 - Referenced to 1 watt (A-weighted): 91 dB
 - Referenced to full output (A-weighted): 112 dB
- Frequency response: 20 Hz to 20 kHz +/- 1 dB (worst case; 4 Ohm load)
- Rated load: From 2.5 Ω - 8 Ω
- Input Connections: Balanced; (accepts XLR, balanced 1/4", unbalanced 1/4")
- Speaker Output Connections: Audiophile grade 5-way binding posts
- Trigger
- Dimensions (H x W x D mm): 45 x 216 x 229
- Weight: 1.4 Kg

Assembled in the USA with Globally Sourced Components

FIVE YEAR WARRANTY