

SMS G24

ACTIVE HIGH-PERFORMANCE
INFRASONIC SUBWOOFER



Speaker type Loudspeaker	Custom-built 24" woofer, 13 cm voice coil, 90 mm linear excursion (world record), with AIA Speaker Management Technology Spezial gefertigter 62 cm Treiber, 90 mm linearer Hub (Weltrekord), 13 cm Schwingspule mit AIA Speaker Management Technologie
Passive Active	Active, built in DSP Amplifier Aktiv, eingebauter DSP Verstärker
Enclosure type Prinzip	Sealed Geschlossen
Cont./peak output Dauer-/Spitzenleistung	120 dB cont. / 122dB peak (@ 30 Hz)
Frequency Range Frequenzbereich	10 Hz - 80 Hz
Air volume displacement Bewege Luft in Litern	9,9 L / in comparison 18" standard cinema subwoofer 1,1 L 9,9 L / zum Vergleich Standard 18" Kinosubwoofer 1,1 L
Directivity horizontal x vertical in Deg°	360°
Output Power Leistung	6.000 W
Power voltage range	85 V - 265 V
Input sensivity, balanced input impedance	2.7V (with gain 32dB), 10k
Analogue Input - Amplifier Analog- eingang - Verstärker	1 x XLR balanced 1 x XLR symmetrisch
Analogue Ouput - Amplifier Analog- ausgang - Verstärker	1 x XLR balanced 1 x XLR symmetrisch
Power connector Strom	Neutrik powerCON True 1 in-out
Network Switch Netzwerkanschluss	2ports Ethernet switch for daisy chain

Controlling Steuerung	OCS Software control, auto discovery
Features Funktionen	Manual Room acoustics-correction, delay, phase, crossover, voicing preset, gain, input sensitivity Manuelle Raumakustikkorrektur, Frequenzweiche, Delay, Phase,
Protection features Schutzfunktionen	Turn-on transients, Over-heating, DC, RF, Short-circuit, mismatched loads, ICL™, PMST™
Enclosure Gehäuse	Internally braced birch ply Innenverstrebtres Birkenperholz
Width Breite	27,56" 700 mm
Hight Höhe	43,31" 1100 mm
Hight with feet Höhe	44,29" 1125 mm
Depth with plug Tiefe mit Stecker	19,69" 500 mm
Depth without grill Tiefe ohne Abdeckung	19,69" 500 mm
Weight Gewicht	242,5 lbs 110 kg
Finish Oberfläche	PU structural paint Robuster Strukturlack schwarz
Custom colour options Farbvarianten	Piano lacquer (12 layers): colour of choice, matt or other finishes upon request, color of choice Echter Klavierlack (12 Schichten): Farbe nach Wahl, Mattlack: Farbe nach Wahl, weitere Oberflächen auf Anfrage
Shape customization Sondergröße	Upon request Auf Anfrage
Mounting Montage	Floor standing with feet

Technical modifications subject to change without further notice | Technische Änderungen vorbehalten