

Torus Power's "TOT" Series consists of three compact models that bring toroidal power conditioning to a new price point. Compact in size, affordable for most applications and packed with features, the TOT Series is an easy choice to improve performance of all audio and video systems.

The **TOT AVR**, rated at 4 amps, provides automatic voltage regulation, thereby enhancing protection against voltage sags, brownouts and surges; plus Smart Ethernet connectivity and RS232 interface. Ideal for home theatre receivers and 2-channel audio systems. Torus TOT AVR will keep the output constant within the range of 220 - 240 VAC +/- 10, with an input voltage of 170-270 VAC.

Technology:

- Toroidal Isolation
- Noise Filtering
- High Instantaneous Current Capability
- Automatic Voltage Regulation
- Smart Ethernet



Specifications:

FACEPLATE	12" BLACK
POWER	920 VA
INPUT	240 VAC (Operating Range 170 - 270V)
OUTPUT	220 - 240 VAC \pm 10V
INPUT FUSE	1 X 4A
INLET	IEC 320-C14
OUTPUT CURRENT	4A
FREQUENCY	47 - 63 Hz
NO. OUTLETS	3
WEIGHT	15.6 kg
DIMENSIONS (W x H x D mm)	318 x 89 x 369

All TOT models feature a courtesy USB charger outlet. Options include a dress aluminium faceplate (Black or Silver) and a 19" rack mount adaptor kit. TOT units include circuit protection through a replaceable varistor. Torus Power non-sacrificial Series Mode Surge Suppression (SMSS) is also available as a factory-installed option.