

RETAIL Price List - Valid From January 2026

Unison Research was founded in 1987 by a group of passionate audiophiles led by Giovanni Maria Sacchetti. After completing his studies in electronics, Giovanni devoted twenty-five years to teaching while at the same time designing and developing amplifiers for Unison Research, including the legendary SIMPLY TWO, achieving great international success in a relatively short time. Designed and produced to high performance and quality standards entirely in Italy, Unison Research is now recognised as the Italian leader in the production of tube amplifiers, and among the top ten in Europe.

STEREO INTEGRATED VALVE AMPLIFIERS

RETAIL
ex VAT

RETAIL
inc VAT

SIMPLY ITALY

Valve complement: 2 x ECC82 2 x EL34
Output stage: Single-ended, ultra-linear, Class-A autobias
Output power: Approx. 10 watts per channel
Input: 4 Line, 1 USB DAC optional
Sub Out line level
Dimensions (W x H x D cm): 26 x 19 x 35
Net weight: 15kg


SIMPLY ITALY Cherry / Black
£1,916.67
£2,300.00
USB DAC DSD 128 for Simply Italy
£229.17
£275.00

SIMPLY ITALY BLACK EDITION

Output power: 10W
Signal valves: 2 x ECC82 Gold Lion
Output power valves: 2 x KT77 Gold Lion
Polarization: electronically controlled pure Class A in ultra-linear configuration with tap at 43% (power valves)
Inputs: 3 line RCA, 1 USB, 1 SPDIF, 1 Toslink
Relay Input Selector with Return GND Technology
Outputs: 1 subwoofer RCA (stereo)
Feedback: selectable between 4dB and 3dB
Bandwidth (-1dB): 15Hz – 50kHz
Dimensions (W x H x D cm): 26 x 18 x 40
Weight: 15Kg


SIMPLY ITALY Black Edition
£2,500.00
£3,000.00

RETAIL Price List - Valid From January 2026

STEREO INTEGRATED VALVE AMPLIFIERS

TRIODE 25

Output Stage: Push-pull, ultra-linear, Class-AB
Output Power: 45W Pentode mode 25W Triode mode
Output Impedance: 6 Ohm
Input: 4 Line (1 Tape) , 1 USB DAC (DSD 128 included)
Input Impedance: 47 kOhm / 50 pF
Output: 1 Tape out, 1 Sub Out RCA stereo
Negative feedback: 5 dB or 1.8 dB
Bias adjustable
Valve complement: 2 x ECC83, 1 x ECC82, 4 x EL34
Power Consumption: 300 watt max
Dimensions (W x H x D cm): 30 x 20 x 45
Weight: 20 Kg



Triode 25 Cherry / Black

£2,833.33

£3,400.00

TRIODE 25 BLACK EDITION

Output Stage: Push-pull, ultra-linear, Class-AB
Output power: 50W pentode mode 30W triode mode
Signal valves: 2 x ECC83 Gold Lion and 1x ECC82 Gold Lion
Output power valves: 4 x KT77 Gold Lion in push pull configuration
Working mode: Triode or ultra-linear with tap at 60% (power valves)
Relay Input Selector with Return GND Technology
Bias adjustable
Inputs: 3 line RCA, 1 USB, 1 SPDIF, 1 Toslink
Outputs: 1 subwoofer RCA (stereo), 1 line out
Feedback: 10dB to 12dB selectable
Bandwidth (-1dB): 10Hz - 50kHz
Dimensions (W x H x D cm): 30 x 20 x 45
Weight: 20 Kg



Triode 25 Black Edition

£3,250.00

£3,900.00

RETAIL Price List - Valid From January 2026

STEREO INTEGRATED VALVE AMPLIFIERS

S6

Valves: 2 x ECC83, 6 x EL34 (Bias adjustable for each power valves)
 Output Stage: single-ended parallel (3x EL34 per channel), ultra-linear
 Class: pure class A
 Output Power: 35 Watt/channel
 Bandwidth: 20 – 30000 Hz (-1dB)
 Output Impedance: 6 Ohm
 Input Impedance: 47 kOhm
 Inputs: 5 line
 Outputs: 1 tape
 Power Consumption: 265VA max
 Dimensions (W x H x D cm): 35 x 21 x 49
 Net Weight: 25kg



S6 Cherry / Black

£3,416.67

£4,100.00

S6 BLACK EDITION

Output power: 40W on 6Ω
 Signal valves: 2 x ECC83 Gold Lion
 Output power valves: 3 x KT77 Gold Lion in parallel for each channel
 Relay Input Selector with Return GND Technology
 Cathode Capacitor Less (CCL) technology, no autobias
 Noiseless as a solid-state amplifier
 Polarisation: pure Class A in ultra-linear configuration with tap at 20% (power valves)
 Bias adjustable for each power valves
 Inputs: 4 line RCA, 1 USB, 1 SPDIF, 1 Toslink
 Outputs: 1 subwoofer RCA (stereo)
 Bandwidth (-1dB): 15Hz - 30kHz
 Dimensions (W x H x D cm): 35 x 21 x 49
 Net Weight: 25kg



S6 Black Edition

£4,500.00

£5,400.00

RETAIL Price List - Valid From January 2026

STEREO INTEGRATED VALVE AMPLIFIERS

PRELUDIO

Output Stage: single ended ultra-linear A class

Output Power: 14W / channel

Inputs: 4 line, 1 tape/monitor

Outputs: 1 tape, 1 subwoofer RCA stereo

Input Impedance: 47 kOhm

Output Impedance: 6 ohm

Feedback factor: 10dB

Bandwidth (-1dB): 20Hz – 35kHz

Valves: 2 x 6550, 2 x ECC82

Power Consumption: 200W max

Dimensions (W x H x D cm): 40 x 18 x 37.5

Net Weight: 18kg



PRELUDIO Cherry / Mahogany

£2,500.00

£3,000.00

SINFONIA

Dual mono design

Output Stage: single ended parallel ultra-linear class A

Output Power: 25W

Inputs: 4 line, 1 tape/monitor

Input Impedance: 47 kOhm

Outputs: 1 tape, 1 subwoofer RCA Stereo

Output Impedance: 4 – 8 ohm

Feedback factor: 14dB

Frequency Response: 20 – 80000 Hz

Valves: 4 x 6550, 2 x ECC82, 2 x ECC83

Remote Control: IR inputs and volume

Power Consumption: 500W max

Dimensions (W x H x D cm): 44 x 21 x 42

Net Weight: 25kg



SINFONIA Cherry / Mahogany

£4,166.67

£5,000.00

SINFONIA Anniversary

As above with output power: 29W

Valves: 4 x KT88, 2 x ECC82, 2 x ECC83 Gold Lion

Copper plate finish



SINFONIA Anniversary Cherry / Mahogany

£5,000.00

£6,000.00

RETAIL Price List - Valid From January 2026

STEREO INTEGRATED VALVE AMPLIFIERS

PERFORMANCE

Dual mono Design

Output Stage: parallel single ended (3X6550 per channel) ultra-linear class A

Output Power: 45 W

Inputs: 4 line, 1 tape/monitor

Input Impedance: 47 kOhm

Outputs: 1 tape, loudspeakers bi-wiring

Output Impedance: 4 – 8 ohm

Feedback factor: 16 dB

Frequency Response: 15 Hz – 25 kHz

Valves: 6 x 6550, 2 x ECC82, 2 x ECC83

Remote Control: IR inputs and volume

Power Consumption: 500VA max

Dimensions (W x H x D cm): 60 x 23.5 x 48

Net Weight: 50kg



PERFORMANCE Cherry / Mahogany

£8,333.33

£10,000.00

PERFORMANCE Anniversary

As above with output power: 48W,

Valves: 6 x KT88, 4 x ECC83 Gold Lion

Copper plate finish



PERFORMANCE anniversary Cherry / Mahogany

£8,916.67

£10,700.00

SIMPLY 845

Valves: 2 x 845 selected, 4 x ECC82/12AU7 selected

Output stage: single-ended, Class A

Output power: 23W

Bandwidth: 20Hz-50kHz, +0dB; -1dB @ 12W

Inputs: 4 line; Outputs 1 tape, 1 subwoofer RCA stereo

Feedback level 14 dB

Output impedance 6 Ω

Input impedance 47 k Ω /100pF

Power consumption 300VA

Dimensions (W x H x D cm): 37 x 26 x 57

Net Weight 30.5kg



SIMPLY 845 Cherry / Mahogany

£6,666.67

£8,000.00

RETAIL Price List - Valid From January 2026

STEREO INTEGRATED VALVE AMPLIFIERS

ABSOLUTE 845 (available via REF dealers only)

Type: Dual mono Stereo Integrated Valve Amplifier

Single ended parallel A class

Output Power: 40 watt / channel

Output Impedance: 4 – 8 Ohm

Inputs: 5 line, 2 tape

Input Impedance: 47 kOhm

Outputs: 2 tape, loudspeakers bi-wiring

Feedback factor: 10 dB

Frequency Response: 20 Hz – 30 kHz

Valves: 4 x 845, 6 x ECC82, 2 x ECC83

Power Consumption: 700 VA

Dimensions (W x H x D cm): 80 x 28 x 60

Net Weight: 90 kg



ABSOLUTE 845 Cherry / Mahogany

£28,333.33

£34,000.00

PRE/POWER VALVE AMPLIFIERS

REFERENCE PRE (available via REF dealers only)

Type: valve preamplifier, dual mono, two chassis

Valves: 2 x 300B, 2 x ECC82, 4 x ECC83, 6 x 6C45P

Phono Valves: 4 x 6C45P, 2 x ECC83

Class: pure class A

Inputs: 4 RCA, 2 XLR, 1 tape, 2 independent phono

Output: 1 RCA, 1 XLR, 1 tape (active), 1 subwoofer (active), Power-on link for REFERENCE Power

Output impedance: 500 ohm

Input impedance: 47 kOhm

Input impedance for Phono: Selectable resistance and capacitance

Pre gain: 20 dB

Phono gain: phono 45 – 55 dB

RIAA: passive ± 0.2 dB

Bandwidth: 10Hz –> 100kHz @ –0.3dB

Negative Feedback: 15 dB line, 0 db Phono

Distortion: 0.1%

Power consumption: 320 W max

Dimensions (W x H x D cm): 45 x 22 x 56

Net Weight: 30Kg



REFERENCE PRE Cherry / Walnut

£14,166.67

£17,000.00

RETAIL Price List - Valid From January 2026

PRE/POWER VALVE AMPLIFIERS

REFERENCE (available via REF dealers only)

Type: Mono Valve Power Amplifier
 Output Stage: double parallel single-ended
 Class: pure class A
 Valves: 4 x 845, 1 x ECC82, 1 x ECC83
 Output Power: 80 watt
 Frequency Response: 20 Hz – 30 kHz
 Feedback factor: 14 dB
 Output Impedance: 4 Ohm e 8 Ohm
 Outputs: loudspeakers bi-wiring
 Inputs: 1 x RCA, 1 x XLR
 Input Impedance: 47 kOhm RCA , 10 kOhm XLR
 Power Consumption: 400 VA approx.
 Dimensions (W x H x D cm): 49 x 28.5 x 77.5
 Net Weight: 70kg



REFERENCE Cherry / Walnut (pair)

£28,750.00

£34,500.00

VALVE PHONO PREAMPLIFIER

SIMPLY PHONO

Stereo Phono Valve preamplifier
 Class: pure class A
 RIAA: passive +/- 0.2 dB (20 Hz / 20 KHz)
 Output Impedance: 800 ohm
 Outputs: 1 x line
 Gain: 52 dB
 THD: 0.4 % at 1 volt output
 Signal to Noise Ratio (S/N): -72 dB
 Inputs: 1 x phono MM or High Output MC (>2mV)
 Input Impedance: 47 Kohm – 100 – 50 – 22 ohm / 100 pF (modifiable)
 Feedback factor: 0 dB
 Valves: 4 x ECC83 / 12AX7
 Power Supply: external
 Dimensions (W x H x D cm): 14 x 10.5 x 29
 Net Weight: 3 Kg (including power supply)



SIMPLY PHONO Cherry / Mahogany + Power Supply

£1,708.33

£2,050.00

RETAIL Price List - Valid From January 2026

VALVE PHONO PREAMPLIFIER

PHONO ONE

Type: Stereo Phono Valve preamplifier

Class: pure A

RIAA : passive +/- 0.1 dB (20 Hz / 20 KHz)

Output Impedance: 800 ohm

Outputs: 1 x line

Gain: 54 dB

THD: 0.1 % @ 1V output

Signal to Noise Ratio (S/N): -80 dB

Inputs: 1 phono MM or MC High Output (>2mV)

Input Impedance: 47 Kohm – 100 – 50 – 22 ohm / 100 – 200 – 320 – 420 pF (modifiable)

Feedback factor: 0 dB.

Valves: 5 x ECC83 / 12AX7

Power supply: external

Dimensions (W x H x D cm): 37.3 x 5.84 x 24.63

Net Weight: 3.6 kg (including power supply)



PHONO ONE Cherry / Mahogany

£2,166.67

£2,600.00

RETAIL Price List - Valid From January 2026

UNICO LINE (available in Black or Silver) HYBRID STEREO INTEGRATED AMPLIFIERS

UNICO Primo

Output power: >80W
 Output stage: 4x POWER MOSFET
 Valve: 1 x ECC83
 Inputs: 5 line RCA (1 phono optional), 1 tape RCA
 Output: 1 tape RCA, 1 subwoofer RCA
 Polarization: Class A Dynamic
 Input stage: Triode Class A
 Sensitivity: 260mV
 Input impedance: 50 kΩ / 47 pF
 Frequency response: -0.1dB@10Hz / -0.5dB@100kHz
 Negative feedback: 10dB
 Damping Factor: >50
 Power consumption: 380W max
 Dimensions (W x H x D cm): 43.5 x 9.5 x 43
 Net weight: 14 kg



UNICO Primo

£1,625.00

£1,950.00

UNICO PRIMO PHONO STAGE (optional)

Input Impedance: 47 kohm / 220 pF (MM) - 100 ohm / 440 pF (MC)
 Gain: MM 40 dB, MC 50 dB
 Gain Selection: +0 dB / +10 dB
 Maximum input voltage: 120 mV @ 1kHz (MM)
 RIAA equalization: active at low frequencies, passive at high frequencies
 THD: 0.09% @ 5mV, 1kHz, MM

Phono stage for UNICO Primo

£133.33

£160.00

RETAIL Price List - Valid From January 2026

UNICO LINE (available in Black or Silver) HYBRID STEREO INTEGRATED AMPLIFIERS

RETAIL
ex VAT

RETAIL
inc VAT

UNICO Nuovo

Output Power: 95W
Output stage: 8X POWER MOSFET
Valve: 2 x ECC83
Input: 5 Line RCA (1 phono optional)
Line Output: 1 tape, 1 sub (with volume control)
Input stage: Pure Class A, double triode in parallel
Frequency response: -0.1dB @ 10Hz, -0.5dB @ 100kHz
Input Impedance: 50kOhm // 47pF
Sensitivity: 260mV RMS
Output Connector: 4 + 4 bi-wiring
Feedback factor: 10dB
THD: 0.15% @ 10W/1kHz
Power consumption: 400W max
Dimensions (W x H x D cm): 43.5 x 9.5 x 43
Net weight: 16kg



UNICO Nuovo

£1,916.67
£2,300.00

UNICO NUOVO PHONO STAGE (optional)

Input Impedance: 47 kohm / 220 pF (MM) - 100 ohm / 440 pF (MC)
Gain: MM 40 dB, MC 50 dB
Gain Selection: +0 dB / +10 dB
Maximum input voltage: 120 mV @ 1kHz (MM)
RIAA equalization: active at low frequencies, passive at high frequencies
THD: 0.09% @ 5mV, 1kHz, MM

Phono stage for UNICO Nuovo

£133.33
£160.00

RETAIL Price List - Valid From January 2026

UNICO LINE (available in Black or Silver) HYBRID STEREO INTEGRATED AMPLIFIERS

RETAIL
ex VAT

RETAIL
inc VAT

UNICO Due

Output power: 100+100W on 8Ω, 180+180W on 4Ω, 290W+290W on 2Ω

Valves: 2 x ECC83 (12AX7)

Filter capacitance: 80,000uF

Output stage: Dynamic Class A 4X power BJT double complementary pair, "Super-Symmetric" configuration

Biassing: Dynamic Class A

Inputs: 3 analogue line (RCA) programmable volume AV input, 1 digital (USB), 1 tape RCA, 1 Phono MM / MC

Analogue line Outputs: 1 tape (RCA), 1 stereo subwoofer (RCA), 1 DAC

Remote: IR volume and source

Dimensions (W x H x D cm): 43.5 x 13 x 43



UNICO Due

£2,333.33
£2,800.00

UNICO 90

Output power: 100+100 W RMS on 8Ω / 160+160 W RMS on 4Ω

Valves: 2X ECC83, 4X ECC81

Output stage: Class AB thermostable, 6X Hexfet

Input stage: Pure A class, double triode totem pole ECC83 and parallel totem pole ECC81. This single stage due to the particular circuitry is able to amplify the input signal and drive directly the power stage

Number of stages: 2, this amplifier due to the particular circuitry is realized by only two stages: input stage and output stage, and use only local feedback

Input: 6 line (3 RCA, 2 XLR, 1 "bypass" RCA)

Line Outputs: 1 tape, 1 sub (volume controlled)

Frequency response: -1dB @ 12Hz e 45kHz -3 dB

Input impedance: 21Kohm // 300pF

Input sensitivity: 860mV RMS

Output connectors: 4 + 4 bi-wiring

Global Feedback factor: 0 dB

THD: < 0.15% @ 1kHz, 1 W < 0.5% @ 1kHz, 10 W

Output resistance: <0.4 ohm, resistive on all audio frequencies

Power Consumption: 550 W (at max power on 8 ohm)

Dimensions (W x H x D cm): 43.5 x 18 x 44

Net weight: 20kg



UNICO 90

£3,750.00
£4,500.00

RETAIL Price List - Valid From January 2026

UNICO LINE (available in Black or Silver) HYBRID STEREO INTEGRATED AMPLIFIERS

RETAIL
ex VAT

RETAIL
inc VAT

UNICO 150

Output power: 150+150 W on 8Ω / 250+250 W on 4Ω
 Valves: 2X ECC83 2X 6H30
 Output stage: Class AB thermostable, 8X Hexfet
 Input stage: Pure A class, double triode totem pole ECC83
 Driver stage: Pure A class, double triode totem pole 6H30
 Input: 6 line (3 unbalanced, 2 balanced, 1 "bypass" unbalanced)
 Line Outputs: 1 tape, 1 sub (volume controlled)
 Frequency response: -1dB @ 12Hz & 45kHz, -3 dB @ 6Hz & 80 kHz
 Input impedance: 24kΩ // 100pF
 Input sensitivity: 860mV RMS
 Output connectors: 4 + 4 bi-wiring
 Global Feedback factor: 0 dB
 Local Feedback factor: 16 dB
 THD: < 0.005% @ 1kHz, 1 W < 0.002% @ 1kHz, 10 W < 0.003% @ 1kHz,
 100 W < 0.002%, from 20 to 20000 Hz, 150 W
 Output resistance: <0.4Ω, resistive on all audio frequencies
 Power Consumption: 550 W (at max power on 8 ohm)
 Dimensions (W x H x D cm): 43.5 x 18 x 44
 Net weight: 25kg



UNICO 150

£4,416.67

£5,300.00

RETAIL Price List - Valid From January 2026

DAC-CD PLAYERS

UNICO CD UNO

Hybrid DAC with CD transport

Valves: 1 x ECC82

Digital Inputs: 1 x USB 2.0: 44.1 – 384 kHz, DSD128, DSD256 Ready Res: 16 to 32 bits; 1 x Toslink™: 44.1 – 96 Res.: 16 to 24 bits; 1 x Bluetooth™ 3.0: 44.1, 48kHz Res: 16 bits

Digital Output: 1x S/PDIF 0.5Vpp on 75 Ohms

Transport: CD-Loader

Display: White graphic OLED 128 X 64

DAC: ESS Sabre ES9018K2M

SNR: 125dB (0dBFS, 1kHz, 192kHz, "A" weighted)

THD+N: 0.0003% (0dBFS, 1kHz, 20Hz-20kHz)

I/V Converter: NE5532AD very low noise

Filters: 3 Digital Filters selectable by R.C: FLT 1: Fast Roll-Off, linear Phase; FLT 2: Fast Roll-Off, minimum Phase; FLT 3: Slow Roll-Off, linear Phase

Solid state Output selectable

Selectable absolute Phase

Dimensions (W x H x D cm): 45 x 13 x 38

Net weight: 10kg



UNICO CD UNO

£2,250.00

£2,700.00

UNICO CD DUE

Hybrid DAC with CD Transport

Valves: 4 x ECC83

Digital Inputs: 1 x USB 2.0: 44.1 – 384 kHz, DSD128, DSD256 Ready Res: 16 to 32 bits; 1 x S/PDIF: 0.5Vpp on 75 Ohms, 44.1 -192 kHz, DSD64 (DoP) Res: 16 to 24 bits; 1 x AES/EBU: 2Vpp on 110 Ohms, 44.1 -192 kHz, DSD64 (DoP) Res: 16 to 24 bits; 1 x Toslink™: 44.1 – 96 Res.: 16 to 24 bits; 1 x Bluetooth™ 3.0: 44.1, 48kHz Res: 16 bits

Digital Output: 1x S/PDIF 0.5Vpp on 75 Ohms; 1x AES/EBU 2Vpp on 110 Ohms; 1x Toslink™

Transport: CD-Loader; Display 128 X 64 White OLED graphic display

DAC: ESS Sabre ES9018K2M SNR: 128dB (0dBFS, 1kHz, 192kHz, "A" weighted) THD+N: 0.0003% (0dBFS, 1kHz, 20Hz-20kHz)

I/V Converter: AD8597/AD8599 ultra-low distortion and ultra-low noise

Valve Output Stage: Number of channels: 2; Output stage: Double Triode, pure class A differential Totem-pole

Output audio connectors: 2 x RCA, 2 x XLR

Filters: 3 Digital Filters selectable by R.C: FLT 1: Fast Roll-Off, linear Phase; FLT 2: Fast Roll-Off, minimum Phase; FLT 3: Slow Roll-Off, linear Phase

Solid state Output selectable; Selectable absolute Phase

Dimensions (W x H x D cm): 45 x 13 x 38; Net weight: 10kg



UNICO CD DUE

£3,166.67

£3,800.00

RETAIL Price List - Valid From January 2026

			RETAIL ex VAT	RETAIL inc VAT
--	--	--	------------------	-------------------

UNICO uPHONO+

MM/MC phono preamplifier
 Analogic moving magnet input (MM) /High output moving coil (MC)
 Low and ultra-low moving coil
 Fixed and variable analogue outputs
 Headphones (16-600Ω): ¼ inch (6.35mm) stereo jack socket
 Type B USB Digital port for pc connection (up to 24 bit / 96 kHz)
 Digital Optical and Coaxial transmission
 Input impedance: MM 47kΩ + 100/200/320 / 420pF; MC 20/50/100/150/250/500 / 1kΩ + 1nF
 Gain: MM 38 dB MC 58dB / 69dB selectable
 Nominal output level 316mVRMS (-10dBV)
 Input sensitivity for nominal output level: MM 3.36mVRMS; MC (58dB) 0,336mVRMS; MC (69dB) 0.1mVRMS
 Signal/Noise Ratio MM -80dB MC (58dB) -64dB MC (69dB) -60dB
 RIAA curve accuracy +/- 0.3dB from 20Hz to 30kHz
 IEC anti-rumble filter -3dB at 20Hz and 6dB/octave
 Overload margin (headroom) 30dB
 THD+N at 1kHz MM 0.018% (10mVRMS in) MC (58dB) 0.12% (1mVRMS in) MC (69dB) 0.12% (1mVRMS in)
 Line output impedance Fixed 824Ω Variable 824Ω
 Headphone stage Output level 2.18VRMS Max THD+N 0.07% (1kHz /32Ω)
 USB A/D Resolution 16/24 bit Sample rates 8, 16, 32, 44.1, 48, 88.2, 96kHz
 Coaxial digital output 0.5Vp-p a 75Ω / 96kHz max.
 Dimensions (W x H x D cm): 21.6 x 8.25 x 25.1 (including feet, connectors and knobs)
 Weight 2.6kg



UNICO uPHONO+			£916.67	£1,100.00
---------------	--	--	---------	-----------

IR wood remote control RC3

IR wood remote control RC3			£229.17	£275.00
----------------------------	--	--	---------	---------