

RETAIL Price List - Valid From March 2026

Unison Research was founded in 1987 by a group of passionate audiophiles led by Giovanni Maria Sacchetti. After completing his studies in electronics, Giovanni devoted twenty-five years to teaching while at the same time designing and developing amplifiers for Unison Research, including the legendary SIMPLY TWO, achieving great international success in a relatively short time. Designed and produced to high performance and quality standards entirely in Italy, Unison Research is now recognised as the Italian leader in the production of tube amplifiers, and among the top ten in Europe.

STEREO INTEGRATED VALVE AMPLIFIERS

RETAIL
ex VAT

RETAIL
inc VAT

SIMPLY ITALY BLACK EDITION

Output power: 10W
 Signal valves: 2 x ECC82 Gold Lion
 Output power valves: 2 x KT77 Gold Lion
 Polarization: electronically controlled pure Class A in ultra-linear configuration with tap at 43% (power valves)
 Inputs: 3 line RCA, 1 USB, 1 SPDIF, 1 Toslink
 Relay Input Selector with Return GND Technology
 Outputs: 1 subwoofer RCA (stereo)
 Feedback: selectable between 4dB and 3dB
 Bandwidth (-1dB): 15Hz – 50kHz
 Dimensions (W x H x D cm): 26 x 18 x 40
 Weight: 15Kg



SIMPLY ITALY Black Edition

£2,500.00

£3,000.00

TRIODE 25 BLACK EDITION

Output Stage: Push-pull, ultra-linear, Class-AB
 Output power: 50W pentode mode 30W triode mode
 Signal valves: 2 x ECC83 Gold Lion and 1x ECC82 Gold Lion
 Output power valves: 4 x KT77 Gold Lion in push pull configuration
 Working mode: Triode or ultra-linear with tap at 60% (power valves)
 Relay Input Selector with Return GND Technology
 Bias adjustable
 Inputs: 3 line RCA, 1 USB, 1 SPDIF, 1 Toslink
 Outputs: 1 subwoofer RCA (stereo), 1 line out
 Feedback: 10dB to 12dB selectable
 Bandwidth (-1dB): 10Hz - 50kHz
 Dimensions (W x H x D cm): 30 x 20 x 45
 Weight: 20 Kg



Triode 25 Black Edition

£3,250.00

£3,900.00

RETAIL Price List - Valid From March 2026

STEREO INTEGRATED VALVE AMPLIFIERS

RETAIL
ex VAT

RETAIL
inc VAT

S6 BLACK EDITION

- Output power: 40W on 6Ω
- Signal valves: 2 x ECC83 Gold Lion
- Output power valves: 3 x KT77 Gold Lion in parallel for each channel
- Relay Input Selector with Return GND Technology
- Cathode Capacitor Less (CCL) technology, no autobias
- Noiseless as a solid-state amplifier
- Polarisation: pure Class A in ultra-linear configuration with tap at 20% (power valves)
- Bias adjustable for each power valves
- Inputs: 4 line RCA, 1 USB, 1 SPDIF, 1 Toslink
- Outputs: 1 subwoofer RCA (stereo)
- Bandwidth (-1dB): 15Hz - 30kHz
- Dimensions (W x H x D cm): 35 x 21 x 49
- Net Weight: 25kg



S6 Black Edition

£4,500.00

£5,400.00



RETAIL Price List - Valid From March 2026

STEREO INTEGRATED VALVE AMPLIFIERS

RETAIL
ex VAT

RETAIL
inc VAT

PRELUDIO

Output Stage: single ended ultra-linear A class
 Output Power: 14W / channel
 Inputs: 4 line, 1 tape/monitor
 Outputs: 1 tape, 1 subwoofer RCA stereo
 Input Impedance: 47 kOhm
 Output Impedance: 6 ohm
 Feedback factor: 10dB
 Bandwidth (-1dB): 20Hz – 35kHz
 Valves: 2 x 6550, 2 x ECC82
 Power Consumption: 200W max
 Dimensions (W x H x D cm): 40 x 18 x 37.5
 Net Weight: 18kg



PRELUDIO Cherry / Mahogany

£2,500.00

£3,000.00

SINFONIA Anniversary

Dual mono design
 Output Stage: single ended parallel ultra-linear class A
 Output Power: 29W
 Inputs: 4 line, 1 tape/monitor
 Input Impedance: 47 kOhm
 Outputs: 1 tape, 1 subwoofer RCA Stereo
 Output Impedance: 4 – 8 ohm
 Feedback factor: 14dB
 Frequency Response: 20 – 80000 Hz
 Valves: 4 x KT88, 2 x ECC82, 2 x ECC83 Gold Lion
 Copper plate finish
 Remote Control: IR inputs and volume
 Power Consumption: 500W max
 Dimensions (W x H x D cm): 44 x 21 x 42
 Net Weight: 25kg



SINFONIA Anniversary Cherry / Mahogany

£5,000.00

£6,000.00

RETAIL Price List - Valid From March 2026

STEREO INTEGRATED VALVE AMPLIFIERS

RETAIL
ex VAT

RETAIL
inc VAT

PERFORMANCE Anniversary

Dual mono Design
 Output Stage: parallel single ended (3X6550 per channel) ultra-linear class A
 Output Power: 48 W
 Inputs: 4 line, 1 tape/monitor
 Input Impedance: 47 kOhm
 Outputs: 1 tape, loudspeakers bi-wiring
 Output Impedance: 4 – 8 ohm
 Feedback factor: 16 dB
 Frequency Response: 15 Hz – 25 kHz
 Valves: 6 x KT88, 4 x ECC83 Gold Lion
 Copper plate finish
 Remote Control: IR inputs and volume
 Power Consumption: 500VA max
 Dimensions (W x H x D cm): 60 x 23.5 x 48
 Net Weight: 50kg



PERFORMANCE anniversary Cherry / Mahogany

£8,916.67

£10,700.00

SIMPLY 845

Valves: 2 x 845 selected, 4 x ECC82/12AU7 selected
 Output stage: single-ended, Class A
 Output power: 23W
 Bandwidth: 20Hz-50kHz, +0dB; -1dB @ 12W
 Inputs: 4 line; Outputs 1 tape, 1 subwoofer RCA stereo
 Feedback level 14 dB
 Output impedance 6 Ω
 Input impedance 47 kΩ/100pF
 Power consumption 300VA
 Dimensions (W x H x D cm): 37 x 26 x 57
 Net Weight 30.5kg



SIMPLY 845 Cherry / Mahogany

£6,666.67

£8,000.00

RETAIL Price List - Valid From March 2026

STEREO INTEGRATED VALVE AMPLIFIERS

RETAIL
ex VAT

RETAIL
inc VAT

ABSOLUTE 845

Type: Dual mono Stereo Integrated Valve Amplifier
 Single ended parallel A class
 Output Power: 40 watt / channel
 Output Impedance: 4 – 8 Ohm
 Inputs: 5 line, 2 tape
 Input Impedance: 47 kOhm
 Outputs: 2 tape, loudspeakers bi-wiring
 Feedback factor: 10 dB
 Frequency Response: 20 Hz – 30 kHz
 Valves: 4 x 845, 6 x ECC82, 2 x ECC83
 Power Consumption: 700 VA
 Dimensions (W x H x D cm): 80 x 28 x 60
 Net Weight: 90 kg



ABSOLUTE 845 Cherry / Mahogany

£28,333.33

£34,000.00

PRE/POWER VALVE AMPLIFIERS

RETAIL
ex VAT

RETAIL
inc VAT

REFERENCE PRE

Type: valve preamplifier, dual mono, two chassis
 Valves: 2 x 300B, 2 x ECC82, 4 x ECC83, 6 x 6C45P
 Phono Valves: 4 x 6C45P, 2 x ECC83
 Class: pure class A
 Inputs: 4 RCA, 2 XLR, 1 tape, 2 independent phono
 Output: 1 RCA, 1 XLR, 1 tape (active), 1 subwoofer (active), Power-on link for REFERENCE Power
 Output impedance: 500 ohm
 Input impedance: 47 kOhm
 Input impedance for Phono: Selectable resistance and capacitance
 Pre gain: 20 dB
 Phono gain: phono 45 – 55 dB
 RIAA: passive ± 0.2 dB
 Bandwidth: 10Hz –> 100KHz @ –0.3dB
 Negative Feedback: 15 dB line, 0 db Phono
 Distortion: 0.1%
 Power consumption: 320 W max
 Dimensions (W x H x D cm): 45 x 22 x 56
 Net Weight: 30Kg



REFERENCE PRE Cherry / Walnut

£14,166.67

£17,000.00

RETAIL Price List - Valid From March 2026

PRE/POWER VALVE AMPLIFIERS

RETAIL
ex VAT

RETAIL
inc VAT

REFERENCE

Type: Mono Valve Power Amplifier
 Output Stage: double parallel single-ended
 Class: pure class A
 Valves: 4 x 845, 1 x ECC82, 1 x ECC83
 Output Power: 80 watt
 Frequency Response: 20 Hz – 30 kHz
 Feedback factor: 14 dB
 Output Impedance: 4 Ohm e 8 Ohm
 Outputs: loudspeakers bi-wiring
 Inputs: 1 x RCA, 1 x XLR
 Input Impedance: 47 kOhm RCA , 10 kOhm XLR
 Power Consumption: 400 VA approx.
 Dimensions (W x H x D cm): 49 x 28.5 x 77.5
 Net Weight: 70kg



REFERENCE Cherry / Walnut (pair)

£28,750.00

£34,500.00

VALVE PHONO PREAMPLIFIER

RETAIL
ex VAT

RETAIL
inc VAT

SIMPLY PHONO

Stereo Phono Valve preamplifier
 Class: pure class A
 RIAA: passive +/- 0.2 dB (20 Hz / 20 KHz)
 Output Impedance: 800 ohm
 Outputs: 1 x line
 Gain: 52 dB
 THD: 0.4 % at 1 volt output
 Signal to Noise Ratio (S/N): -72 dB
 Inputs: 1 x phono MM or High Output MC (>2mV)
 Input Impedance: 47 Kohm – 100 – 50 – 22 ohm / 100 pF (modifiable)
 Feedback factor: 0 dB
 Valves: 4 x ECC83 / 12AX7
 Power Supply: external
 Dimensions (W x H x D cm): 14 x 10.5 x 29
 Net Weight: 3 Kg (including power supply)



SIMPLY PHONO Cherry / Mahogany - inc power supply

£1,708.33

£2,050.00

RETAIL Price List - Valid From March 2026

VALVE PHONO PREAMPLIFIER

RETAIL
ex VAT

RETAIL
inc VAT

PHONO ONE

Type: Stereo Phono Valve preamplifier
 Class: pure A
 RIAA : passive +/- 0.1 dB (20 Hz / 20 KHz)
 Output Impedance: 800 ohm
 Outputs: 1 x line
 Gain: 54 dB
 THD: 0.1 % @ 1V output
 Signal to Noise Ratio (S/N): -80 dB
 Inputs: 1 phono MM or MC High Output (>2mV)
 Input Impedance: 47 Kohm – 100 – 50 – 22 ohm / 100 – 200 – 320 – 420 pF (modifiable)
 Feedback factor: 0 dB.
 Valves: 5 x ECC83 / 12AX7
 Power supply: external
 Dimensions (W x H x D cm): 37.3 x 5.84 x 24.63
 Net Weight: 3.6 kg (including power supply)



PHONO ONE Cherry / Mahogany

£2,166.67

£2,600.00



RETAIL Price List - Valid From March 2026

**UNICO LINE (available in Black or Silver)
HYBRID STEREO INTEGRATED AMPLIFIERS**

RETAIL
ex VAT

RETAIL
inc VAT

UNICO Primo

Output power: >80W
 Output stage: 4x POWER MOSFET
 Valve: 1 x ECC83
 Inputs: 5 line RCA (1 phono optional), 1 tape RCA
 Output: 1 tape RCA, 1 subwoofer RCA
 Polarization: Class A Dynamic
 Input stage: Triode Class A
 Sensitivity: 260mV
 Input impedance: 50 kΩ / 47 pF
 Frequency response: -0.1dB@10Hz / -0.5dB@100kHz
 Negative feedback: 10dB
 Damping Factor: >50
 Power consumption: 380W max
 Dimensions (W x H x D cm): 43.5 x 9.5 x 43
 Net weight: 14 kg



UNICO Primo

£1,625.00

£1,950.00

UNICO PRIMO PHONO STAGE (optional)

Input Impedance: 47 kohm / 220 pF (MM) - 100 ohm / 440 pF (MC)
 Gain: MM 40 dB, MC 50 dB
 Gain Selection: +0 dB / +10 dB
 Maximum input voltage: 120 mV @ 1kHz (MM)
 RIAA equalization: active at low frequencies, passive at high frequencies
 THD: 0.09% @ 5mV, 1kHz, MM

Phono stage for UNICO Primo

£133.33

£160.00

RETAIL Price List - Valid From March 2026

**UNICO LINE (available in Black or Silver)
HYBRID STEREO INTEGRATED AMPLIFIERS**

RETAIL
ex VAT

RETAIL
inc VAT

UNICO Nuovo

Output Power: 95W
 Output stage: 8X POWER MOSFET
 Valve: 2 x ECC83
 Input: 5 Line RCA (1 phono optional)
 Line Output: 1 tape, 1 sub (with volume control)
 Input stage: Pure Class A, double triode in parallel
 Frequency response: -0.1dB @ 10Hz, -0.5dB @ 100kHz
 Input Impedance: 50kOhm // 47pF
 Sensitivity: 260mV RMS
 Output Connector: 4 + 4 bi-wiring
 Feedback factor: 10dB
 THD: 0.15% @ 10W/1kHz
 Power consumption: 400W max
 Dimensions (W x H x D cm): 43.5 x 9.5 x 43
 Net weight: 16kg



UNICO Nuovo

£1,916.67

£2,300.00

UNICO NUOVO PHONO STAGE (optional)

Input Impedance: 47 kohm / 220 pF (MM) - 100 ohm / 440 pF (MC)
 Gain: MM 40 dB, MC 50 dB
 Gain Selection: +0 dB / +10 dB
 Maximum input voltage: 120 mV @ 1kHz (MM)
 RIAA equalization: active at low frequencies, passive at high frequencies
 THD: 0.09% @ 5mV, 1kHz, MM

Phono stage for UNICO Nuovo

£133.33

£160.00

RETAIL Price List - Valid From March 2026

UNICO LINE (available in Black or Silver)
HYBRID STEREO INTEGRATED AMPLIFIERS

RETAIL
ex VAT

RETAIL
inc VAT

UNICO Due

Output power: 100+100W on 8Ω, 180+180W on 4Ω, 290W+290W on 2Ω

Valves: 2 x ECC83 (12AX7)

Filter capacitance: 80,000uF

Output stage: Dynamic Class A 4X power BJT double complementary pair, "Super-Symmetric" configuration

Biasing: Dynamic Class A

Inputs: 3 analogue line (RCA) programmable volume AV input, 1 digital (USB), 1 tape RCA, 1 Phono MM / MC

Analogue line Outputs: 1 tape (RCA), 1 stereo subwoofer (RCA), 1 DAC

Remote: IR volume and source

Dimensions (W x H x D cm): 43.5 x 13 x 43



UNICO Due

£2,333.33

£2,800.00

UNICO 90

Output power: 100+100 W RMS on 8Ω / 160+160 W RMS on 4Ω

Valves: 2X ECC83, 4X ECC81

Output stage: Class AB thermostable, 6X Hexfet

Input stage: Pure A class, double triode totem pole ECC83 and parallel totem pole ECC81. This single stage due to the particular circuitry is able to amplify the input signal and drive directly the power stage

Number of stages: 2, this amplifier due to the particular circuitry is realized by only two stages: input stage and output stage, and use only local feedback

Input: 6 line (3 RCA, 2 XLR, 1 "bypass" RCA)

Line Outputs: 1 tape, 1 sub (volume controlled)

Frequency response: -1dB @ 12Hz e 45kHz -3 dB

Input impedance: 21Kohm // 300pF

Input sensitivity: 860mV RMS

Output connectors: 4 + 4 bi-wiring

Global Feedback factor: 0 dB

THD: < 0.15% @ 1kHz, 1 W < 0.5% @ 1kHz, 10 W

Output resistance: <0.4 ohm, resistive on all audio frequencies

Power Consumption: 550 W (at max power on 8 ohm)

Dimensions (W x H x D cm): 43.5 x 18 x 44

Net weight: 20kg



UNICO 90

£3,750.00

£4,500.00

RETAIL Price List - Valid From March 2026

UNICO LINE (available in Black or Silver)
HYBRID STEREO INTEGRATED AMPLIFIERS

RETAIL
ex VAT

RETAIL
inc VAT

UNICO 150

Output power: 150+150 W on 8Ω / 250+250 W on 4Ω
 Valves: 2X ECC83 2X 6H30
 Output stage: Class AB thermostable, 8X Hexfet
 Input stage: Pure A class, double triode totem pole ECC83
 Driver stage: Pure A class, double triode totem pole 6H30
 Input: 6 line (3 unbalanced, 2 balanced, 1 "bypass" unbalanced)
 Line Outputs: 1 tape, 1 sub (volume controlled)
 Frequency response: -1dB @ 12Hz & 45kHz, -3 dB @ 6Hz & 80 kHz
 Input impedance: 24kΩ // 100pF
 Input sensitivity: 860mV RMS
 Output connectors: 4 + 4 bi-wiring
 Global Feedback factor: 0 dB
 Local Feedback factor: 16 dB
 THD: < 0.005% @ 1kHz, 1 W < 0.002% @ 1kHz, 10 W < 0.003% @ 1kHz,
 100 W < 0.002%, from 20 to 20000 Hz, 150 W
 Output resistance: <0.4Ω, resistive on all audio frequencies
 Power Consumption: 550 W (at max power on 8 ohm)
 Dimensions (W x H x D cm): 43.5 x 18 x 44
 Net weight: 25kg



UNICO 150

£4,416.67

£5,300.00



RETAIL Price List - Valid From March 2026

DAC-CD PLAYERS

RETAIL
ex VAT

RETAIL
inc VAT

UNICO CD UNO

Hybrid DAC with CD transport
 Valves: 1 x ECC82
 Digital Inputs: 1 x USB 2.0: 44.1 – 384 kHz, DSD128, DSD256 Ready Res: 16 to 32 bits; 1 x Toslink™: 44.1 – 96 Res.: 16 to 24 bits; 1 x Bluetooth™ 3.0: 44.1, 48kHz Res: 16 bits
 Digital Output: 1x S/PDIF 0.5Vpp on 75 Ohms
 Transport: CD-Loader
 Display: White graphic OLED 128 X 64
 DAC: ESS Sabre ES9018K2M
 SNR: 125dB (0dBFS, 1kHz, 192kHz, "A" weighted)
 THD+N: 0.0003% (0dBFS, 1kHz, 20Hz-20kHz)
 I/V Converter: NE5532AD very low noise
 Filters: 3 Digital Filters selectable by R.C: FLT 1: Fast Roll-Off, linear Phase; FLT 2: Fast Roll-Off, minimum Phase; FLT 3: Slow Roll-Off, linear Phase
 Solid state Output selectable
 Selectable absolute Phase
 Dimensions (W x H x D cm): 45 x 13 x 38
 Net weight: 10kg



UNICO CD UNO

£2,250.00

£2,700.00

UNICO CD DUE

Hybrid DAC with CD Transport
 Valves: 4 x ECC83
 Digital Inputs: 1 x USB 2.0: 44.1 – 384 kHz, DSD128, DSD256 Ready Res: 16 to 32 bits; 1 x S/PDIF: 0.5Vpp on 75 Ohms, 44.1 -192 kHz, DSD64 (DoP) Res: 16 to 24 bits; 1x AES/EBU: 2Vpp on 110 Ohms, 44.1 -192 kHz, DSD64 (DoP) Res: 16 to 24 bits; 1 x Toslink™: 44.1 – 96 Res.: 16 to 24 bits; 1 x Bluetooth™ 3.0: 44.1, 48kHz Res: 16 bits
 Digital Output: 1x S/PDIF 0.5Vpp on 75 Ohms; 1x AES/EBU 2Vpp on 110 Ohms; 1x Toslink™
 Transport: CD-Loader; Display 128 X 64 White OLED graphic display
 DAC: ESS Sabre ES9018K2M SNR: 128dB (0dBFS, 1kHz, 192kHz, "A" weighted) THD+N: 0.0003% (0dBFS, 1kHz, 20Hz-20kHz)
 I/V Converter: AD8597/AD8599 ultra-low distortion and ultra-low noise
 Valve Output Stage: Number of channels: 2; Output stage: Double Triode, pure class A differential Totem-pole
 Output audio connectors: 2 x RCA, 2 x XLR
 Filters: 3 Digital Filters selectable by R.C: FLT 1: Fast Roll-Off, linear Phase; FLT 2: Fast Roll-Off, minimum Phase; FLT 3: Slow Roll-Off, linear Phase
 Solid state Output selectable; Selectable absolute Phase
 Dimensions (W x H x D cm): 45 x 13 x 38; Net weight: 10kg



UNICO CD DUE

£3,166.67

£3,800.00

RETAIL Price List - Valid From March 2026

UNICO PRE/POWER AMPLIFIERS

RETAIL
ex VAT

RETAIL
inc VAT

UNICO PRE

New Unico flagship preamplifier featuring a completely new design

Type: Fully balanced hybrid preamplifier

Valves: 2 × ECC83 / 12AX7 Gold Lion

Operating mode: Class A

Output stage: Solid state

Volume control: Infrared

Analogue inputs: 3 × Line RCA; 3 × Line XLR; 1 × Phono MM / MC; 1 × Line In

Digital inputs: 1 × USB; 2 × Toslink; 2 × S/PDIF

Outputs: 2 × RCA; 1 × XLR

Dual subwoofer output

DAC: Sabre ES9018K2M

USB: USB-B input, PCM up to 384 kHz, native DSD up to 256×, DoP up to 128×

Toslink: 2 × inputs up to 192 kHz

S/PDIF: 2 × inputs up to 192 kHz

Available in Velvet Gold and Midnight Black

Dimensions: 45 × 43 × 14 cm

Net weight: 11 kg



UNICO PRE

£4,583.33

£5,500.00

UNICO DM

New Unico flagship power amplifier featuring a completely new design

Output power (@ 1 kHz, 1% THD): 220 W continuous @ 8 Ω (stereo); 340 W continuous @ 4 Ω (stereo); 370 W continuous @ 2 Ω (stereo, limited by protections); 670 W peak @ 2 Ω (stereo); 650 W continuous @ 8 Ω (mono); 650 W continuous @ 4 Ω (mono)

Input stage: Pure Class A

Dual-triode stage (ECC82 / 12AU7) Gold Lion

Output stage: A.S.H.A. Technology; Class A-AB; Three complementary MOSFET pairs

Input connectors: 1 × unbalanced RCA; 1 × balanced XLR; 1 × remote power-on input

Output connectors: 4 + 4 binding posts for bi-wiring; 1 × remote power-on output

Available in Velvet Gold and Midnight Black

Dimensions (W×D×H): 46 × 42 × 21 cm 18 × 17 × 8 inches

Net weight: 33 kg



UNICO DM

£6,458.33

£7,750.00

RETAIL Price List - Valid From March 2026

			RETAIL ex VAT	RETAIL inc VAT
--	--	--	------------------	-------------------

UNICO uPHONO+

MM/MC phono preamplifier
 Analogic moving magnet input (MM) /High output moving coil (MC)
 Low and ultra-low moving coil
 Fixed and variable analogue outputs
 Headphones (16-600Ω): ¼ inch (6.35mm) stereo jack socket
 Type B USB Digital port for pc connection (up to 24 bit / 96 kHz)
 Digital Optical and Coaxial transmission
 Input impedance: MM 47kΩ + 100/200/320 / 420pF; MC 20/50/100/150/250/500 / 1kΩ + 1nF
 Gain: MM 38 dB MC 58dB / 69dB selectable
 Nominal output level 316mVRMS (-10dBV)
 Input sensitivity for nominal output level: MM 3.36mVRMS; MC (58dB) 0,336mVRMS; MC (69dB) 0.1mVRMS
 Signal/Noise Ratio MM -80dB MC (58dB) -64dB MC (69dB) -60dB
 RIAA curve accuracy +/- 0.3dB from 20Hz to 30kHz
 IEC anti-rumble filter -3dB at 20Hz and 6dB/octave
 Overload margin (headroom) 30dB
 THD+N at 1kHz MM 0.018% (10mVRMS in) MC (58dB) 0.12% (1mVRMS in) MC (69dB) 0.12% (1mVRMS in)
 Line output impedance Fixed 824Ω Variable 824Ω
 Headphone stage Output level 2.18VRMS Max THD+N 0.07% (1kHz /32Ω)
 USB A/D Resolution 16/24 bit Sample rates 8, 16, 32, 44.1, 48, 88.2, 96kHz
 Coaxial digital output 0.5Vp-p a 75Ω / 96kHz max.
 Dimensions (W x H x D cm): 21.6 x 8.25 x 25.1 (including feet, connectors and knobs)
 Weight 2.6kg



UNICO uPHONO+			£916.67	£1,100.00
---------------	--	--	---------	-----------

IR wood remote control RC3

IR wood remote control RC3			£229.17	£275.00
----------------------------	--	--	---------	---------

USB DAC DSD 128 for Simply Italy

USB DAC DSD 128 for Simply Italy			£229.17	£275.00
----------------------------------	--	--	---------	---------